


FRONT PERSPECTIVE
6" 500 PCS PER CASE
70 CASES PER PALLET



CROSS SECTION

SPECIFICATIONS

PRODUCT DESCRIPTION: BIODEGRADABLE STAKE

MATERIAL OF COMPOSITION: POLYPROPYLENE BASED RESIN FROM 100% RECYCLED MATERIALS WITH AN ADDITIVE TO CAUSE BREAKDOWN AND DEGRADATION

APPLICABLE STANDARDS: THIS PRODUCT IS PRODUCED TO BREAK DOWN AND DEGRADE IN ACCORDANCE WITH ASTM OXO-BIODEGRADABILITY STANDARD, SPECIFICALLY ASTM D6954

OXO-DEGRADATION BY-PRODUCT: CARBON-DIOXIDE, WATER AND HUMUS

OXO-DEGRADATION PERIOD: MAINTAIN HOLDING POWER IN THE GROUND FOR 24 MONTHS AFTER WHICH IT WILL BIODEGRADE AND DISAPPEAR COMPLETELY


STORAGE: ECODUTY STAKES HAVE A SHELF LIFE OF 36 MONTHS BEFORE LOSS OF STRUCTURE DUE TO EXPOSURE TO OXYGEN MOLECULES WHICH REDUCES THEIR DURABILITY OVER TIME

MANUFACTURER NOTES:

1. 6" STAKES ARE DESIGNED FOR TILLED OR SOFTER SOILS TO PENETRATE INTO HARD SOILS BELOW SURFACE. 6" STAKES HAVE THREE TIMES THE HOLDING POWER OF 6" STEEL STAPLES

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5287-002



ECODUTY STAKES (EDS-6D)

6" OXO-BIODEGRADABLE STAKE - DETAIL